

# SICHERUNGSSPLINT - PIN, COTTER


Lagernde Dimensionen

Dimensionsschlüssel: AN 380-X-Y ( $\phi=X/32$ ,  $l=Y/4$ )

AN 381-X-Y ( $\phi=X/32$ ,  $l=Y/16$ )

Material: kadmierter Kohlenstoffstahl oder \*) korrosionsfreier, antimagnetischer Stahl

MS24665 COTTER PINS  
AN380 AND AN381 COTTER PINS



Nr:	Bezeichnungen			$\phi$ (Zoll)	l (Zoll)
1	AN 380-1-2	AN 381-1-8 *)	MS 24665-5 MS 24665-22 *)	1/32	1/2
2	AN 380-1-3	AN 381-1-12 *)	MS 24665-7 MS 24665-24 *)	1/32	3/4
3	AN 380-1-4	AN 381-1-16 *)	MS 24665-9 MS 24665-26 *)	1/32	1
4	AN 380-2-1	AN 381-2-6 *)	MS 24665-130 MS 24665-149 *)	1/16	3/8
5	AN 380-2-2	AN 381-2-8 *)	MS 24665-132 MS 24665-151 *)	1/16	1/2
6	AN 380-2-3	AN 381-2-12 *)	MS 24665-134 MS 24665-153 *)	1/16	3/4
7			MS 24665-154 *)	1/16	7/8
8	AN 380-2-4	AN 381-2-16 *)	MS 24665-136 MS 24665-155 *)	1/16	1
9	AN 380-2-8	AN 381-2-32 *)	MS 24665-143 MS 24665-162 *)	1/16	2
10			MS 24665-208 MS 24665-227 *)	5/64	1/2
11			MS 24665-210 MS 24665-229 *)	5/64	3/4
12			MS 24665-212 MS 24665-231 *)	5/64	1
13	AN 380-3-3	AN 381-3-12 *)	MS 24665-283 MS 24665-300 *)	3/32	3/4
14	AN 380-3-4	AN 381-3-16 *)	MS 24665-285 MS 24665-302 *)	3/32	1
15	AN 380-3-5	AN 381-3-20 *)	MS 24665-287 MS 24665-304 *)	3/32	1 1/4
16	AN 380-3-8	AN 381-3-32 *)	MS 24665-292 MS 24665-309 *)	3/32	2
17	AN 380 -4-4	AN 381-4-16 *)	MS 24665-353 MS 24665-370 *)	1/8	1
18	AN 380-4-5	AN 381-4-20 *)	MS 24665-355 MS 24665-372 *)	1/8	1 1/4
19	AN 380-4-6	AN 381-4-24 *)	MS 24665-357 MS 24665-374 *)	1/8	1 1/2
20	AN 380-4-7	AN 381-4-28 *)	MS 24665-359 MS 24665-376 *)	1/8	1 3/4
21	AN 380-4-8	AN 381-4-32 *)	MS 24665-360 MS 24665-377 *)	1/8	2
22			MS 24665-361 MS 24665-378 *)	1/8	2 1/4
23	AN 380-5-6	AN 381-5-25 *)	MS 24665-423 MS 24665-441 *)	5/32	1 1/2
24	AN 380-5-10	AN 381-5-40 *)	MS 24665-428 MS 24665-446 *)	5/32	2 1/2